



(888) 420 - 5675

650 HORSEPOWER LOW NOX MOBILE

BOILER ROOM



BOILER INFORMATION

One (1) 650 horsepower mobile boiler room complete with one (1) 650 HP Low NOx steam boiler, combination natural gas or No. 2 fuel oil fired, design pressure 250 psi, capable of producing 22,425 lbs. of steam per hour from and at 212 degrees F.

The boiler comes complete with gas train, oil train, No. 2 fuel oil pump, second low water cut-off, pressure controls, flame safeguard control, relief valves, feed-water valves, blowdown valves, a fully modulating Powerflame Low Nox burner equipped with Auto Flame controls.

Connection Sizes:

- Main steam outlet - 6", 300# flanged
- Natural gas connection - 3", 150# flanged
- Maximum inlet pressure to gas regulator - 10 PSIG.
- #2 fuel oil connections - 1 1/2" (Storage tank by others)
- Atomizing steam connection - 1 1/2"
- Feedwater - 2" MPT
- Propane tank connection size for pilot, if oil fired, 3/8" flared.
- Propane tank provided by others.

Fuel Consumption:

- Natural gas - 27,300 SCFH
- No. 2 fuel oil - 195 GPH

Also Included:

- One (1) deaerator system
- Two (2) feedwater pumps
- One (1) twin water softener system
- One (1) blowdown system
- One (1) chemical pump
- Electrical switch gear
- One (1) propane hose and regulator for pilot connection, if oil fired
- One (1) main steam stop valve
- One (1) operator's manual
- Pre-piped & enclosed in a 53' trailer.

Voltage and Amperage Requirements:

- 480 volts 100 amp service, 3 phase